



TABLE OF DIMENSIONS
(DIMENSIONS IN MM)

Type	HP	C	R	H	D	A	Adjustable Propeller		Fixed propeller		Balance wheel diam.
							F	S	F	S	
A	3—4	205	570	80	240	430	690	920	800	900	385
A	4—5	245	650	70	270	465	800	1100	1000	1190	440
A	5—7	255	700	70	290	465	850	1100	1000	1140	490
A	7—10	310	725	75	305	465	850	1100	1040	1180	490

TECHNICAL DATA

Type	HP	Cyl. diam mm	Length of stroke mm	Cyl. volume cm ³	R. P. M.	Fuel consumption per HP-hr	For fixed propeller					For adjustable propeller					Weight of engine without propeller		
							Propeller shaft		Propellersleeve		Propeller diam. mm.	Propeller shaft		Reversing tube	Propellersleeve			Propeller diam. mm.	
							Length mm.	Diam. mm.	Length mm.	Diam. mm.		Length mm.	Diam. mm.		Length mm.	Diam. mm.			Length mm.
A	3—4	110	130	1.200	600	300	1.500	27	500	47	400	1.500	24	1.300	29	500	47	440	205
A	4—5	125	150	1.800	550	280	1.500	30	500	60	510	1.500	27	1.300	32	500	60	480	298
A	5—7	135	156	2.200	550	275	1.500	32	500	60	525	1.500	30	1.300	35	500	60	510	335
A	7—10	148	164	2.800	600	260	1.500	32	500	60	530	1.500	30	1.300	35	500	60	530	358

Without guarantee