



DIMENSION TABLE

(Measures in millimeters)

| Type | H. P. | C | R | H | D | A | Adjustable screw | | Fixed screw | | Diameter of balance wheel |
|------|-------|-----|-----|----|-----|-----|------------------|------|-------------|------|---------------------------|
| | | | | | | | F | S | F | S | |
| A | 3—4 | 205 | 570 | 80 | 240 | 430 | 690 | 920 | 800 | 900 | 385 |
| A | 4—5 | 245 | 650 | 70 | 270 | 465 | 800 | 1100 | 1000 | 1190 | 440 |
| A | 5—7 | 255 | 700 | 70 | 290 | 465 | 850 | 1100 | 1000 | 1140 | 490 |
| A | 7—10 | 310 | 725 | 75 | 305 | 465 | 850 | 1100 | 1040 | 1180 | 490 |

CHARACTERISTICS

| Type | H. P. | Cyl. diam. mm. | Pist. stroke mm. | Cyl. volume cm ³ | Rev. per min. | Fuel consumption H. P. and hour about gr. | For fixed screw | | | | | For adjustable screw | | | | | Weight of engine without screw Kos. | | |
|------|-------|----------------|------------------|-----------------------------|---------------|---|-----------------|-----------|--------------------|-----------|-----------------|----------------------|-----------|------------|-----------|--------------------|-------------------------------------|-----------------|-----------|
| | | | | | | | Screw shaft | | Screw shaft casing | | Screw diam. mm. | Screw shaft | | Rev. tube | | Screw shaft casing | | Screw diam. mm. | |
| | | | | | | | Length mm. | Diam. mm. | Length mm. | Diam. mm. | | Length mm. | Diam. mm. | Length mm. | Diam. mm. | Length mm. | | | Diam. mm. |
| A | 3—4 | 110 | 130 | 1.200 | 600 | 300 | 1.500 | 27 | 500 | 47 | 400 | 1.500 | 24 | 1.300 | 29 | 500 | 47 | 440 | 205 |
| A | 4—5 | 125 | 150 | 1.800 | 550 | 280 | 1.500 | 30 | 500 | 60 | 510 | 1.500 | 27 | 1.300 | 32 | 500 | 60 | 480 | 298 |
| A | 5—7 | 135 | 156 | 2.200 | 550 | 275 | 1.500 | 32 | 500 | 60 | 525 | 1.500 | 30 | 1.300 | 35 | 500 | 60 | 510 | 335 |
| A | 7—10 | 148 | 164 | 2.800 | 600 | 260 | 1.500 | 32 | 500 | 60 | 530 | 1.500 | 30 | 1.300 | 35 | 500 | 60 | 530 | 358 |

Without engagement!