



## DIMENSIONSTABELL (MÅTT I MM.)

Typ	Hkr.	C	R	H	D	A	Vridbar propeller		Fast propeller		Balanshjulsdiam.
							F	S	F	S	
A	3-4	205	570	80	240	430	690	920	800	900	385
A	4-5	245	650	70	270	465	800	1100	999	1190	430
A	5-7	255	700	70	290	465	850	1100	999	1140	490
A	7-10	260	725	75	305	465	850	1100	1040	1180	490

## TEKNISKA DATA

Typ	Hkr.	Cyl.-diam. mm.	Slaglängd mm.	Cyl.-volym cm. <sup>3</sup>	Varv per min.	Bränsleförbrukning pr hk.tim. ca gr.	För fast propeller				För vridbar propeller				Motorsvikt utan propeller kg.				
							Propelleraxel		Propellerhylsa		Propellerdiam. mm.	Propelleraxel		Omkastn.-rör		Propellerhylsa		Propellerdiam. mm.	
							Längd mm.	Diam. mm.	Längd mm.	Diam. mm.		Längd mm.	Diam. mm.	Längd mm.		Diam. mm.	Längd mm.		Diam. mm.
A	3-4	110	130	1.200	600	300	1.500	27	500	47	400	1.500	24	1.300	29	500	47	445	205
A	4-5	125	150	1.800	550	280	1.500	30	500	60	510	1.500	27	1.300	32	500	60	520	298
A	5-7	135	156	2.200	550	275	1.500	32	500	60	525	1.500	30	1.300	35	500	60	510	335
A	7-10	148	164	2.800	600	260	1.500	32	500	60	530	1.500	30	1.300	35	500	60	585	358

*Utan förbindelse!*